LARGE IC CUSHION

### PAPER ROLL SPECIAL



## PAPER, HANDLED

- ▶ 12000 lb. Capacity
- ► Enhanced Dust & Debris Filtration
- ► Specialized Counterweight
- ► Force-Cooled Wet Disc Brakes



50-8FGC55U-PRS

## PAPER ROLL HANDLING, PERFECTED

#### THE TOYOTA PAPER ROLL SPECIAL FORKLIFT. The product:

heavy, awkward, easily damaged. The environment: dusty, dirty, did we mention dusty? Paper handling presents exacting demands. The Paper Roll Special meets them safely and with thoughtful efficiency. Equipped to stack and maneuver heavy paper rolls, it's the perfect solution for paper mills, printing plants, newspaper production and similar applications. Paperwork? Done.

#### **PAPER ROLL SPECIAL ADVANTAGES**

► SYSTEM OF ACTIVE STABILITY™ (SAS)

automatically detects potentially unsafe conditions and engages additional safety features for increased operator protection and reduced product and forklift damage

CLAMP RELEASE INTERLOCK helps prevent

accidental release of clamp

► AUTOMATIC CLAMP LEVELING positions clamp vertical to paper roll, improving efficiency and productivity and limiting product damage

► SHORTENED WHEELBASE, LOAD DISTANCE & RIGHT-ANGLE STACKING RADIUS for greater

maneuverability

► FORCE-COOLED WET DISC BRAKES reduce maintenance cost and downtime with an expected lifespan of 10 years/20,000 hours\*



\*Actual results may vary by application and usage

- ► LARGE RADIATOR & COOLING FAN handle damp, humid paper- and pulp-processing environment
- ► ENGINE & RADIATOR FILTRATION SYSTEMS are designed to keep out excess dust and debris common in paper-handling applications





 CAPACITY
 WHEELBASE
 LOAD CENTER

 12000 LBS.
 70.5 IN.
 24 IN.

#### **INDUSTRIES**



#### STANDARD FEATURES

#### DURABILITY

- Control Area Network (CAN-bus) communication
- Wide Visible Full-Free Lift Three Stage Mast (FSV)
- Fully-stamped steel side panels
- Full-floating front axle

- Moisture-resistant electric connectors
- High cooling capacity radiator
- Low-maintenance battery
- · Large-capacity engine cooling fan
- 8" cyclone air cleaner
- Plate-iron front fenders

- Anti-restart ignition key switch
- Stamped steel engine hood
- Radiator screen
- External hydraulic oil cooler
- Force-cooled wet disc brakes
- Full oil-charged lift cylinder

#### SUPPORT

- System of Active Stability<sup>™</sup> (SAS)
- Operator Presence Sensing System (OPSS)
- Bolt-on overhead guard

- · Key lowering interlock
- Electric horn
- · Neutral start safety switch
- Key off/headlight off system
- Speed control

#### **PERFORMANCE**

- EPA/CARB-certified engine
- Toyota 3.7 liter, 4-cylinder, OHV LP engine (1FS)
- Distributorless ignition system
- Treaded cushion tires (front & rear)
- Wide tread
- Automatic clamp leveling
- UL-approved model type "LP"
- Full-floating powertrain
- LED headlights

- LCD Multi-Function Display includes:
- Data log, fuel, and operation information
   w/ QR Code output
- Master warning, wheel, direction, and mast tilt indicators
- Various hour meters
- Engine coolant temperature gauge
- Fuel gauge (gasoline only)
- Check engine light
- Engine oil pressure warning light

- OPSS activation light
- Parking brake indicator
- SAS/OPSS warning light
- Alternator with built-in regulator (60A)
- Automatic transmission with oil cooler
- Electric shift control
- Hydraulic system tuned for clamping attachments

#### **ERGONOMICS**

- Dash-mounted instrument display
- 11.8"-dia., 2-spoke steering wheel
- Load-sensing power steering
- Cowl-mounted hydraulic control levers with rubber boot covers
- 12"-long dual operator assist grips
- · Heavy-duty non-slip rubber floor mat
- Low, wide entry steps
- Vinyl 4-way adjustable full-suspension seat
- Double action parking brake (hand)
- Oversized cup holder
- Non-cinching seatbelt
- Load-sensing power steering
- Integrated headlight & turn signal lever

#### **SERVICEABILITY**

- Easy access no tools required floorboard
- Engine hood assist damper with lock device
- Air cleaner discharge valve
- Easy-lift engine hood with wide 75° opening
- Easy access to common service items such as filters & dipsticks
- Engine protection system

#### OPTIONAL EQUIPMENT

- Intelli-Shift
- Mini-lever controls with ErgoShift
- · Synchronized steering
- EZ Pedal foot directional control
- Combination brake & inching pedal
- Steering wheel with knob
- Hydraulic accumulators 1 or 2 quarts
- LED front combination lights

- Strobe lights
- LED rear combination lights
- LED rear work light
- LED reverse-activated rear work light
- Cloth 4-way adjustable full-suspension seat
- Swivel seat
- Orange seatbelt

- Box fin radiator
- Pre-cleaner for air intake
- Rearview mirrors
- 12-Volt power supply
- Rear assist grip with horn button
- Back up alarms
- 5-way hydraulics
- SEnS

#### TRUCK SPECIFICATIONS

#### MODEL NUMBER

|                                                                                  |                          |                           |                              |                | MODEL NUMBER               |  |
|----------------------------------------------------------------------------------|--------------------------|---------------------------|------------------------------|----------------|----------------------------|--|
| GENERAL DATA                                                                     |                          |                           |                              |                | 50-8FGC55U-PRS             |  |
| Load Capacity                                                                    |                          |                           |                              | lb (kg)        | 12000 (5500)               |  |
| Load Center                                                                      |                          |                           |                              | in (mm)        | 24 (600)                   |  |
| Power Type                                                                       |                          |                           |                              |                | LPG                        |  |
| Operator Position                                                                |                          |                           |                              |                | Seated Rider               |  |
| Tire Type Front / Rear                                                           |                          |                           | Front / Rear                 |                | Cushion / Cushion          |  |
| Wheels (x = driven) Front / Rear                                                 |                          |                           | Front / Rear                 |                | 2x/2                       |  |
| EXTERIOR DIMENSIONS                                                              |                          |                           |                              |                | 50-8FGC55U-PRS             |  |
| Maximum Fork Height (top of forks)                                               |                          |                           |                              | in (mm)        | N/A                        |  |
| Free-Lift (top of forks)                                                         |                          |                           |                              | in (mm)        | N/A                        |  |
| Fork Size (T x W x L)                                                            |                          |                           |                              | in (mm)        | No Forks                   |  |
| Fork Spread Max. / Min. (outer edge to edge)                                     |                          |                           |                              | in (mm)        | 46.1 (1170) / 11.8 (300)   |  |
| Tilt Range (forward / backward)                                                  |                          |                           |                              | deg            | 5/6                        |  |
| Length to Fork Face                                                              |                          |                           |                              | in (mm)        | N/A                        |  |
| Overall Width                                                                    |                          |                           |                              | in (mm)        | 55.9 (1420)                |  |
| Mast Lowered Height                                                              |                          |                           |                              | in (mm)        | 86.6 (2200)                |  |
| Mast Extended Height (top of load backrest)                                      |                          |                           |                              | in (mm)        | 174.6 (4435)               |  |
| Overhead Guard Height                                                            |                          |                           |                              | in (mm)        | 83.5 (2120)                |  |
| Turning Radius (inside / outside)                                                |                          |                           |                              | in (mm)        | 93.5 (2380)                |  |
| Load Distance Basic Right-Angle Stacking Aisle Width                             |                          |                           |                              | in (mm)        | N/A                        |  |
| Basic Right-Angle                                                                | e Stackii                | ng Aisle Widt             | h                            | in (mm)        | _                          |  |
| PERFORMANCE DATA                                                                 |                          |                           |                              |                | 50-8FGC55U-PRS             |  |
| Speeds³                                                                          |                          | um Travel                 | Full Load                    | mph (km/h)     | 13.0 (21.0) / 13.0 (21.0)  |  |
|                                                                                  | (forwar                  | d / reverse)              | No Load                      | mph (km/h)     | 13.0 (21.0) / 13.0 (21.0)  |  |
|                                                                                  | Lifting                  |                           | Full Load                    | fpm (mm/sec)   | 85 (430)                   |  |
|                                                                                  | Litting                  |                           | No Load                      | fpm (mm/sec)   | 87 (440)                   |  |
|                                                                                  | Lowering                 |                           | Full Load                    | fpm (mm/sec)   | 102 (520)                  |  |
|                                                                                  | Lowering                 |                           | No Load                      | fpm (mm/sec)   | 93 (470)                   |  |
| Drawbar Pull                                                                     | Maximum                  |                           | Full Load                    | Ib (kg)        | 9900 (4500)                |  |
|                                                                                  |                          |                           | No Load                      | Ib (kg)        | 3300 (1500)                |  |
| Gradeability <sup>1</sup>                                                        | Full Lo                  |                           | Full Load                    | %              | 25                         |  |
|                                                                                  |                          |                           |                              | %              | 34                         |  |
| No Load                                                                          |                          |                           | No Load                      | 70             | 10                         |  |
| TRUCK WEIGHTS                                                                    |                          |                           |                              |                | 50-8FGC55U-PRS             |  |
| Total Weight                                                                     |                          |                           |                              | lb (kg)        | 17510 (7940)               |  |
| Weight                                                                           | Full Load (front / rear) |                           |                              | lb (kg)        | 25490 (1160) / 4140 (1880) |  |
| Distribution                                                                     | No Load (front / rear)   |                           |                              | lb (kg)        | 6020 (2730) / 11490 (5210) |  |
| TIRES                                                                            |                          |                           |                              |                | 50-8FGC55U-PRS             |  |
| Tires                                                                            | Number (front / rear)    |                           |                              |                | 2/2                        |  |
|                                                                                  | Size                     |                           | Front                        |                | 22 x 12 x 16               |  |
|                                                                                  |                          |                           | Rear                         |                | 18 x 8 x 12-1/8            |  |
| Wheelbase                                                                        |                          |                           |                              | in (mm)        | 70.5 (1790)                |  |
| Tread Width (front / rear)                                                       |                          |                           |                              | in (mm)        | 43.9 (1115) / 43.5 (1105)  |  |
| (full load) Center                                                               |                          | um with Load              |                              | in (mm)        | 3.3 (85)                   |  |
|                                                                                  |                          | r of Wheelbase            |                              | in (mm)        | 5.7 (145)                  |  |
| Brake Service (foot) / Parking                                                   |                          |                           | Hydraulic <wet> / Hand</wet> |                |                            |  |
| POWER SYSTEM                                                                     |                          |                           |                              |                | 50-8FGC55U-PRS             |  |
| Battery (5-hour rating)                                                          |                          |                           |                              | V / Ah         | 12 / 35                    |  |
| Internal<br>Combustion<br>Engine <sup>3</sup>                                    |                          | Make / Model              |                              |                | IFS-US                     |  |
|                                                                                  |                          | Rated Horsepower<br>@ rpm |                              | SAE HP         | 88 @ 2530                  |  |
|                                                                                  |                          |                           |                              | (kW)           | (66 @ 2530)                |  |
|                                                                                  |                          | Rated Torque @ rpm —      |                              | SAE ft-lb      | 212 @ 1600                 |  |
|                                                                                  |                          |                           |                              | (N-m)          | (288 @ 1600)               |  |
|                                                                                  |                          | Number of Cylinders       |                              |                | 4                          |  |
|                                                                                  |                          | Piston Displacement       |                              | cu in (cc)     | 224 (3685)                 |  |
|                                                                                  |                          | Fuel Tank Capacity        |                              | US gal (liter) | _                          |  |
| Francosis -!                                                                     |                          | Туре                      |                              |                | Automatic                  |  |
| Transmission                                                                     |                          | Speeds (forward / reverse |                              | e)             | 1/1                        |  |
| Auxiliary Hydraulic<br>Function Specifications<br>(for attachments) <sup>2</sup> |                          | Max. Operating Pressure   |                              | psi (kg/cm2)   | 2630 (185)                 |  |
|                                                                                  |                          | Max. Flow Rate            |                              | gpm (lpm)      | 33.8 (128)                 |  |
|                                                                                  |                          |                           |                              |                |                            |  |

- Computed values. Performance of LPG fuel system may be less than performance of standard model shown.

  Values taken at Hydraulic Control Valve. Does not take in to consideration losses through most plumbing (hosing, fittings, QDs, etc.).

  Estimated based on preliminary performance test data







# "I'M HERE TO MAKE SURE YOUR FORKLIFTS DON'T TAKE VACATION DAYS."

Butch – 360 Technician, ProLift, Cincinnati, Ohio



#### HELP IS ALWAYS HERE WITH TOYOTA 360 SUPPORT.

The industry's best and most comprehensive dealer network quickly delivers Toyota Certified Technicians to your work site. These specially trained technicians can also help assess your warehouse and facility needs to recommend the right equipment for the job. And with the largest fleet of material handling equipment, Toyota 360 keeps your business running at full speed.

ToyotaForklift.com/360-Support



YOUR BUSINESS IS RIDING ON IT.

Some product features described herein are optional. Please consult your dealer for specifications. Details of specifications and equipment are based on information available at time of printing and may change without notice. Photos may not reflect physical trucks.

